



ITEM/MODELO: POOL LIGHT BLUE MIX Size/Formato: 31,6X0,04 (2,5X2,5) Nominal Size/Medida fabricación: 316mmX396mmX0,4mm Color: BLUE Group/Familia: Glass Mosaic With Silicone Dot/Mosaico De Vidrio Con Punto De Silicona	
--	---

Technical Data · Caractéristique Technique · Características Técnicas	Norm · Norme · Norma	Estándar Valeur · Valor
Water Absorption · Absortion d'eau · Absorción de Agua	UNE-EN-ISO 10545-3	0 %
Scratch Hardness · Résistance aux Rayures · Dureza al Rayado (MOHS)	EN 101	3 - 4
Chemical Resistance · Résistance Chimique · Resistencia Química	UNE-EN-ISO 10545-13	GA / GHA / GLA
Frost Resistance · Résistance au Gel · Resistencia a la Helada	UNE-EN-ISO 10545-12	OK
Stain Resistance · Résistance aux Tâches · Resistencia a las Manchas	UNE-EN-ISO 10545-14	CLASS 5 · CLASSE 5 · CLASE 5
Nonslip Treatment Technical Data Caractéristique Technique Traitement Antiderapant Características Tratamiento Antideslizante	Norm · Norme · Norma	Estándar Valeur · Valor
Tortus Method "Dinamic Slider" Methode Tortus "Dérapant D	ISO / DIS 10545-17	CLASS 2 CLASSE 2 fh > = 0,4 CLASE 2
Slip Resistance Résistance a L'antiderapant Resistencia al Des	DIN 51097 	CLASS A+B+C CLASSE A+B+C (a > 33) CLASE A+B+C
Method USRV without Polishing. Friction Pendulum USRV Méthode sans Polissage. Pendule de Frottement Método USRV sin Pulir. Péndulo de Fricción	UNE-ENV 12633:2003	CLASS 3 CLASSE 3 CLASE 3

Signed by Technical Director:


ROCK CERAMIC, S.L.
 C/ Apeadero Mijangas, 3 - Ed. Ind. Sis. Quarts
 P.O. Box 237 - 12700 ONDA (Castellón) - Spain
 Tel.: 34 964 626 125 - Fax: 34 934 626 141
 e-mail: info@rockceramic.es - www.rockceramic.es
 N.I.F. B-12603833